

## **Patent Abstracts of Japan**

**PUBLICATION NUMBER** 

60096793

**PUBLICATION DATE** 

30-05-85

APPLICATION DATE

31-10-83

APPLICATION NUMBER

58202740

APPLICANT: ISUZU MOTORS LTD:

INVENTOR: MATSUDA MITSUHIRO;

INT.CL.


: C25D 13/12 B23K 11/10 C23F 15/00

C25D 13/20

TITLE

: RUST INHIBITING METHOD OF PANEL

**CONNECTION PART** 



ABSTRACT: PURPOSE: To increase the bonding strength of a panel joined part and to contrive to enhance the rust inhibiting property at said part, by adhering a conductive resin sheet to one panel and subsequently superposing the other panel to said sheet and fusion bonding both panels before electrodeposition coating.

> CONSTITUTION: To the connection part of one panel 1' to which the connection part has to be formed, a resin sheet which has a width wider than that of said connection part and comprises PE having fusion bonding property and is made conductive by mixing carbon black, is adhered through a sticking agent applied to the single surface thereof in such a state that the resin sheet 2 is protruded to the inner surface of a V-shaped joined part. Subsequently, the connection part of the other panel 1 is superposed thereon and temporarily adhered by fusion bonding or spot welding to form a panel assembly to which electrodeposition coating is, in turn, applied to form a film 3. In the next step, the film 3 is baked at a high temp. to fill the inner surface cross point of the V-shaped united part along with the above mentioned resin sheet 2 and both panels 1, 1' are strongly adhered while a good rust inhibiting surface is formed.

COPYRIGHT: (C)1985,JPO&Japio